

# SINGLE CAB

SPECIFICATIONS



**ISUZU**  
Delivers

# SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
<b>Engines</b>								
Engine Capacity (cc)	1998	1998	2405	2405	2499	2499	2499	2999
Cylinders	4	4	4	4	4	4	4	4
Compression	9.2:1	9.2:1	9.6:1	9.6:1	18.5:1	18.5:1	18.3:1	17.5:1
Bore x Stroke (mm)	86x86	86x86	87.5x100	87.5x100	93x92	93x92	95.4x87.4	95.4x104.9
Fuel Type	Petrol	Petrol	Petrol	Petrol	Diesel	Diesel	Diesel	Diesel
Fuel Supply - Injection System	MPFI	MPFI	MPFI	MPFI	Direct Injection	Direct Injection	Common Rail	Common Rail
Power (kW) @ r/min	88@5400	88@5400	94@4800	94@4800	58@3800	58@3800	85@3600	120@3600
Torque (Nm) @ r/min	174@3200	174@3200	207@3200	207@3200	170@1800	170@1800	280@1800-2200	360@1800-2800
Turbocharger	-	-	-	-	LP Compensator	LP Compensator	•	•
Intercooler	-	-	-	-	-	-	•	•
Engine Oil Sump Guard	-	•	•	•	-	•	•	•
<b>Transmission</b>								
Differential Lock : Electro-pneumatic	O	O	•	•	O	O	•	•
4WD Button Select - 2 Speed Transfer Case	-	-	-	•	-	-	•	-
Front Axle - Auto Locking Shift on the Fly	-	-	-	•	-	-	•	-
Transfer Case Guard	-	-	-	•	-	-	•	-
Gear Ratio: 1st	4.357	4.357	4.357	4.357	4.357	4.357	4.008	4.326
Gear Ratio: 2nd	2.502	2.502	2.502	2.502	2.502	2.502	2.301	2.557
Gear Ratio: 3rd	1.501	1.501	1.501	1.501	1.501	1.501	1.427	1.490
Gear Ratio: 4th	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Gear Ratio: 5th	0.809	0.809	0.809	0.809	0.809	0.809	0.745	0.795
Gear Ratio: Reverse	3.970	3.970	3.970	3.970	3.970	3.970	3.651	3.942
Axle Ratio: Final Drive	4.555	4.875	4.875	4.777	4.300	4.555	3.909	3.727
Low Range Ratio	-	-	-	2.482	-	-	2.482	-
<b>Masses, Dimensions and other Key Measurements</b>								
GVM (kg)	2800	2800	2800	2900	2800	2800	2900	2800
GCM (kg)	3750	3750	3750	4000	3750	3750	4000	3750
Tare (kg)	1460	1560	1620	1660	1560	1650	1780	1800
Payload (kg)	1340	1240	1180	1240	1240	1150	1120	1000
GAW (kg) - Front	1200	1300	1300	1300	1200	1300	1300	1300
GAW (kg) - Rear	1680	1680	1680	1680	1680	1680	1680	1680
Legal Towing Capacity (kg): Unbraked Trailer	750	750	750	750	750	750	750	750
Legal Towing Capacity (kg): Trailer with Overrun Brake	950	950	950	1100	950	950	1100	950
Overall Length (mm)	5120	5120	5150	5120	5120	5120	5120	5150

# SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
Overall Length (mm) (Incl. Rear Step/Tow Bar Where Applicable)	5120	5120	5150	5120	5120	5120	5120	5150
Overall Width (mm)	1800	1800	1800	1800	1800	1800	1800	1800
Overall Width (mm) (Incl. Mirrors)	2060	2060	2060	2060	2060	2060	2060	2060
Overall Height (mm)	1630	1710	1735	1710	1630	1710	1710	1735
Wheelbase (mm)	3050	3050	3050	3050	3050	3050	3050	3050
Ground Clearance (mm) (Centre Differential)	184	213	224	213	185	213	213	206
Track: Front (mm)	1460	1515	1520	1515	1460	1515	1515	1520
Track: Rear (mm)	1460	1520	1525	1520	1460	1520	1520	1525
Loadbox: Length (mm)	2270	2270	2270	2270	2270	2270	2270	2270
Loadbox: Width (mm)	1530	1530	1530	1530	1530	1530	1530	1530
Loadbox: Depth (mm)	450	450	450	450	450	450	450	450
Fuel Tank Capacity (litres)	76	76	76	76	76	76	76	76
Approach Angle	25°	35°	36°	35°	25°	35°	35°	36°
Departure Angle	27°	25°	21°	25°	27°	25°	25°	21°
Breakover Angle	160°	157°	157°	157°	160°	157°	157°	157°
Turning Circle: Tyres (m)	11.8	12.4	12.4	12.4	11.8	12.4	12.4	12.4
Turning Circle: Body (m)	12.5	13.1	13.1	13.1	12.5	13.1	13.1	13.1
Steering Lock-to-lock	3.38	3.38	3.26	3.26	3.38	3.26	3.26	3.26
Steering Ratio	18.2	18.2	18.3	18.3	18.2	18.3	18.3	18.3
Wading Depth	400mm	500mm	500mm	500mm	400mm	500mm	500mm	500mm
<b>Vehicle Safety and Security</b>								
ABS: 4 Sensor 3 Channel Anti-lock Braking System and EBD	-	-	•	-	-	-	-	•
Brake Load Sensing Proportioning Valve	•	•	-	•	•	•	•	-
SRS Airbag: Driver and Passenger	-	-	•	-	-	-	-	•
Seat Belt Front: Inertia Reel Locking (3-point) with Adjustable Shoulder	•	•	-	•	•	•	•	-
Seat Belt Front: Inertia Reel Locking (3-point) with Adjustable Shoulder & Pretensioner	-	-	•	-	-	-	-	•
Seat Belt Front: Centre Lap Belt (2-point)	•	•	-	•	•	•	•	-
Head Restraints Front - Adjustable & Active	-	-	•	-	-	-	-	•
Head Restraints Front - Adjustable	•	•	-	•	•	•	•	-
Side Door Impact Beams	•	•	•	•	•	•	•	•
Aspherical Driver's Side Mirror with Split	-	-	•	-	-	-	-	•
Central Locking: Remote Activation (with Selective Unlock)	-	-	•	-	-	-	-	•
Audible Alarm System	0	0	•	0	0	0	0	•
Transponder Immobiliser System (Key Housed)	•	•	•	•	•	•	•	•

# SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
Automatic Door Lock: Over 30km/h	-	-	•	-	-	-	-	•
Spare Wheel Lock (Matched to Vehicle Lock Set)	•	•	•	•	•	•	•	•
<b>Wheels, Suspension and Brakes</b>								
Wheel Size	5.5Jx14	7Jx15	7Jx15	7Jx15	5.5Jx14	7Jx15	7Jx15	7Jx15
Tyre Size	195R14C	215R15	245/75R15C	215R15	195R14C	215R15	215R15	245R15C
Steel Wheels	•	-	-	-	•	-	-	-
Styled Steel Wheels	-	•	-	•	-	•	•	-
Alloy Wheels: 15"	-	0	•	0	-	0	0	•
Alloy Wheels: 16"	-	-	0	-	-	-	-	0
Front Disc Diameter	256mm	280mm	280mm	280mm	280mm	280mm	280mm	280mm
Rear Drum Diameter	254mm	295mm	295mm	295mm	254mm	295mm	295mm	295mm
Front and Rear Shocks	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised
Suspension - Front	Coil spring	High Ride Torsion Bar	High Ride Torsion Bar	Torsion Bar	Coil spring	High Ride Torsion Bar	Torsion Bar	High Ride Torsion Bar
<b>Interior Comfort and Convenience</b>								
Bench Seat: Front	•	•	-	•	•	•	•	-
Bucket Front - Reclining	-	-	•	-	-	-	-	•
Map Pockets: Behind Front Seats	-	-	•	-	-	-	-	•
Full Vinyl Seat Covering	•	•	-	•	•	•	•	-
Full Cloth Seat Covering	0	0	•	0	0	0	0	•
Leather / Cloth Combination Trim	-	-	-	-	-	-	-	-
Floor Cover: Vinyl with Driver Heel Mat	•	•	-	•	•	•	•	-
Floor Cover: Carpet with Driver Heel Mat	-	-	•	-	-	-	-	•
Driver's Left Footrest	•	•	•	•	•	•	•	•
Steering: Power Assist	•	•	•	•	•	•	•	•
Leather Steering	-	-	-	-	-	-	-	-
Steering Column: Tilt	-	•	•	•	-	•	•	•
Power Windows - Front with Auto Down For Driver	-	-	•	-	-	-	-	•
Air Conditioner	-	-	•	-	-	-	-	•
Cabin Air Filter (Pollen)	-	-	•	-	-	-	-	•
Windscreen Tinted with Shadeband	•	•	•	•	•	•	•	•
Side Glass Tinted	•	•	•	•	•	•	•	•
Sliding Rear Window (Tinted)	-	0	•	0	-	0	0	•
Assist Grip Handle: Front	•	•	•	•	•	•	•	•
Front Gearshift Console with 2 Cupholders	-	•	•	•	-	•	•	•
Centre Storage Console	-	-	•	-	-	-	-	•
Illuminated & Lockable Glove Box	•	•	•	•	•	•	•	•

# SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
Day / Night Rear View Mirror	•	•	•	•	•	•	•	•
Map Reading Lights - Front	-	-	•	-	-	-	-	•
Room Lamp Door Operated	•	•	•	•	•	•	•	•
Room Lamp Delay - Fade Up / Down	-	-	•	-	-	-	-	•
Headlamps "On" Warning Buzzer	•	•	•	-	•	•	-	•
Coolant Level Warning Buzzer	•	•	•	•	•	•	-	-
Digital Clock	-	•	•	•	-	•	•	•
Windscreen Wipers - Intermittent	•	•	•	•	•	•	•	•
Remote Fuel Flap Release	•	•	•	•	•	•	•	•
<b>Exterior Features</b>								
Metallic Paint	•	•	•	•	•	•	•	•
Cab Protector	•	•	-	•	•	•	•	-
Roll Bar	-	-	•	-	-	-	-	•
Front Fog Lamps	-	-	•	-	-	-	-	•
Mudguards Front and Rear	•	•	•	•	•	•	•	•
Front Bumper: Grey Grained	•	•	•	•	•	•	•	•
High Opulent Full Width Rear Step Bumper with Tow Pack	-	-	•	-	-	-	-	•
Body Side Mouldings: Grey	-	-	•	-	-	-	-	•
Wheel Arch Protector: Grey	•	•	-	-	•	•	-	-
Wheel Arch Mouldings: Grey Grained	-	-	•	•	-	-	•	•
Rear View Mirror: Manual Black Folding	•	•	-	•	•	•	•	-
Rear View Mirror: Power Black Folding	-	-	•	-	-	-	-	•
<b>In Car Entertainment</b>								
Radio/CD/MP3 + CD Changer Control	0	0	•	0	0	0	0	•
Front Speakers - Front Doors	0	0	•	0	0	0	0	•
Antenna - B Sting	0	0	•	0	0	0	0	•
<b>Warranty, Service and Support</b>								
Service Plan - 5 Year / 90 000km	-	-	•	•	•	•	•	•
Service	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Oil Change	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Warranty	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km
Roadside Assistance	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km
Anti-corrosion	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

Standard	•
Optional	0
Not Available	-

# EXTENDED CAB

SPECIFICATIONS



**ISUZU**  
Delivers

# EXTENDED CAB SPEC



Model	KB 360 V6	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
<b>Opulence</b>	LX	LE	LX	LX
<b>Drive Configuration</b>	4x2	4x2	4x2	4x4
<b>Engines</b>				
Engine Capacity (cc)	3565	2499	2999	2999
Cylinders	6	4	4	4
Compression	10.2:1	18.3:1	17.5:1	17.5:1
Bore x Stroke (mm)	94 x 85.6	95.4 x 87.4	95.4 x 104.9	95.4 x 104.9
Fuel Type	Petrol	Diesel	Diesel	Diesel
Fuel Supply - Injection System	MPFI	Common Rail	Common Rail	Common Rail
Power (kW) @ r/min	155@5600	85@3600	120@3600	120@3600
Torque (Nm) @ r/min	300@3200	280@1800-2200	360@1800-2800	360@1800-2800
Turbocharger	-	•	•	•
Intercooler	-	•	•	•
Engine Oil Sump Guard	•	•	•	•
<b>Transmission</b>				
Differential Lock : Electro-pneumatic	•	•	•	•
4WD Button Select - 2 Speed Transfer Case	-	-	-	•
Front Axle - Auto Locking Shift on the Fly	-	-	-	•
Transfer Case Guard	-	-	-	•
Gear Ratio: 1st	3.753	4.008	4.326	4.326
Gear Ratio: 2nd	2.258	2.301	2.557	2.557
Gear Ratio: 3rd	1.373	1.427	1.490	1.490
Gear Ratio: 4th	1.000	1.000	1.000	1.000
Gear Ratio: 5th	0.729	0.745	0.795	0.795
Gear Ratio: Reverse	3.672	3.651	3.942	3.942
Axle Ratio: Final Drive	4.300	4.111	3.727	3.727
Low Range Ratio	-	-	-	2.482
<b>Masses, Dimensions and other Key Measurements</b>				
GVM (kg)	2800	2800	2800	2900
GCM (kg)	3750	3750	3750	4000
Tare (kg)	1735	1770	1845	1935
Payload (kg)	1065	1030	955	965
GAW (kg) - Front	1300	1300	1300	1300
GAW (kg) - Rear	1680	1680	1680	1680
Legal Towing Capacity (kg): Unbraked Trailer	750	750	750	750
Legal Towing Capacity (kg): Trailer with Overrun Brake	950	950	950	1100
Overall Length (mm)	5150	5150	5150	5150
Overall Length (mm) (Incl. Rear Step/Tow Bar Where Applicable)	5150	5150	5150	5150
Overall Width (mm)	1800	1800	1800	1800

# EXTENDED CAB SPEC



Model	KB 360 V6	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LX	LE	LX	LX
Drive Configuration	4x2	4x2	4x2	4x4
Overall Width (mm) (Incl. Mirrors)	2060	2060	2060	2060
Overall Height (mm)	1745	1745	1745	1745
Wheelbase (mm)	3050	3050	3050	3050
Ground Clearance (mm) (Centre Differential)	224	224	206	206
Track: Front (mm)	1520	1520	1520	1520
Track: Rear (mm)	1525	1525	1525	1525
Loadbox: Length (mm)	1380	1380	1380	1380
Loadbox: Width (mm)	1460	1460	1460	1460
Loadbox: Depth (mm)	480	480	480	480
Fuel Tank Capacity (litres)	76	76	76	76
Approach Angle	36°	36°	36°	36°
Departure Angle	21°	21°	21°	21°
Breakover Angle	158°	158°	158°	158°
Turning Circle: Tyres (m)	12.4	12.4	12.4	12.4
Turning Circle: Body (m)	13.1	13.1	13.1	13.1
Steering Lock-to-lock	3.26	3.26	3.26	3.26
Steering Ratio	18.3	18.3	18.3	18.3
Wading Depth	500mm	500mm	500mm	500mm
<b>Vehicle Safety and Security</b>				
SRS Airbags: Driver and Passenger	•	•	•	•
ABS: 4 Sensor 3 Channel Anti-lock Braking System and EBD	•	•	•	•
Seat Belt Front: Inertia Reel Locking (3-point) with Adjustable Shoulder & Pretensioner	•	•	•	•
Head Restraints Front - Adjustable & Active	•	•	•	•
Side Door Impact Beams	•	•	•	•
Aspherical Driver's Side Mirror with Split	•	•	•	•
Central Locking: Remote Activation (with Selective Unlock)	•	•	•	•
Audible Alarm System	•	•	•	•
Transponder Immobiliser System (Key Housed)	•	•	•	•
Automatic Door Lock: Over 30km/h	•	•	•	•
Spare Wheel Lock (Matched to Vehicle Lock Set)	•	•	•	•
<b>Wheels, Suspension and Brakes</b>				
Wheel Size	7Jx16	7Jx15	7Jx16	7Jx16
Tyre Size	245/70R16C	245/75R15C	245/70R16C	245/70R16C
Alloy Wheels: 15"	-	•	-	-
Alloy Wheels: 16"	•	0	•	•
Front Disc Diameter	280mm	280mm	280mm	280mm
Rear Drum Diameter	295mm	295mm	295mm	295mm



# EXTENDED CAB SPEC



Model	KB 360 V6	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LX	LE	LX	LX
Drive Configuration	4x2	4x2	4x2	4x4
Front and Rear Shocks	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised
Suspension - Front	High Ride Torsion Bar	High Ride Torsion Bar	High Ride Torsion Bar	Torsion Bar
<b>Interior Comfort and Convenience</b>				
Bucket Front - Reclining, Tilt and Slide with Height Adjustable Driver Seat	•	•	•	•
Map Pockets: Behind Front Seats	•	•	•	•
Full Cloth Seat Covering	-	•	-	-
Leather / Cloth Combination Trim	•	-	•	•
Silver Finish Hard Trim	•	-	•	•
Floor Cover: Carpet - with Driver Heel Mat	•	•	•	•
Driver's Left Footrest	•	•	•	•
Cruise Control	•	-	•	•
Steering: Power Assist	•	•	•	•
Urethane Steering with Airbag	-	•	-	-
Leather Steering with Airbag	•	-	•	•
Steering Column: Tilt	•	•	•	•
Power Windows - Front with Auto Down For Driver	•	•	•	•
Air Conditioner	•	•	•	•
Cabin Air Filter (Pollen)	•	•	•	•
Windscreen Tinted with Shadeband	•	•	•	•
Side Glass Tinted	•	•	•	•
Sliding Rear Window (Tinted)	•	•	•	•
Assist Grip Handle: Front	•	•	•	•
Front Gearshift Console with 2 Cupholders	•	•	•	•
Centre Storage Console	•	•	•	•
Illuminated & Lockable Glove Box	•	•	•	•
Rear Storage Bins	•	•	•	•
Day / Night Rear View Mirror	•	•	•	•
Map Reading Lights - Front	•	•	•	•
Room Lamp Door Operated	•	•	•	•
Room Lamp Delay - Fade Up / Down	•	•	•	•
Sunvisor Driver & Passenger Side	•	•	•	•
Vanity Mirror Passenger Side	•	•	•	•
Power Outlet On Dash	•	•	•	•
Headlamps "On" Warning Buzzer	•	•	•	•
Coolant Level Warning Buzzer	•	-	-	-
Digital Clock	•	•	•	•

# EXTENDED CAB SPEC



Model	KB 360 V6	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LX	LE	LX	LX
Drive Configuration	4x2	4x2	4x2	4x4
Fuel Consumption & Outside Temperature Meter	-	-	•	•
Windscreen Wipers - Intermittent	-	•	-	-
Windscreen Wipers - Variable Intermittent	•	-	•	•
Remote Fuel Flap Release	•	•	•	•
Smoker Pack - Instrument Panel Mounted (Illuminated)	•	•	•	•
<b>Exterior Features</b>				
Metallic Paint	•	•	•	•
Front Fog Lamps	•	•	•	•
Roll Bar	•	•	•	•
Mudguards Front And Rear	•	•	•	•
Front Bumper: Grey Grained	-	•	-	-
Front Bumper: Body Colour	•	-	•	•
Running Board - Cab Length	•	-	•	•
High Opulent Full Width Rear Step Bumper with Tow Pack	•	•	•	•
Body Side Mouldings: Grey	-	•	-	-
Body Side Mouldings: Body Colour	•	-	•	•
Wheel Arch Mouldings: Grey Grained	-	•	-	-
Wheel Arch Mouldings: Body Colour	•	-	•	•
Rear View Mirror: Black Power Folding	-	•	-	-
Rear View Mirror: Chrome Power Folding with Indicator	•	-	•	•
<b>In Car Entertainment</b>				
Radio/CD/MP3 + CD Changer Control	•	•	•	•
Front Speakers - Front Doors	•	•	•	•
Tweeters - Front Doors	•	-	•	•
Antenna - B Sting	•	•	•	•
<b>Warranty, Service and Support</b>				
Service Plan - 5Year / 90 000km	•	•	•	•
Service	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Oil Change	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Warranty	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km
Roadside Assistance	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km
Anti-corrosion	3 Years	3 Years	3 Years	3 Years

Standard	•
Optional	O
Not Available	-

# DOUBLE CAB

SPECIFICATIONS



**ISUZU**  
Delivers

# DOUBLE CAB SPEC



Model	KB 240	KB 240	KB 360 V6	KB 360 V6	KB 360 V6	KB 250 D-TEQ	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LE	LE	LX	LX	LX	LE	LE	LX	LX	LX	LX
Drive Configuration	4x2	4x4	4x2	4x4	4x4 auto	4x2	4x4	4x2	4x2 auto	4x4	4x4 auto
<b>Engines</b>											
Engine Capacity (cc)	2405	2405	3565	3565	3565	2499	2499	2999	2999	2999	2999
Cylinders	4	4	6	6	6	4	4	4	4	4	4
Compression	9.6:1	9.6:1	10.2:1	10.2:1	10.2:1	18.3:1	18.3:1	17.5:1	17.5:1	17.5:1	17.5:1
Bore x Stroke (mm)	87.5x100	87.5x100	94x85.6	94x85.6	94x85.6	95.4x87.4	95.4x87.4	95.4x104.9	95.4x104.9	95.4x104.9	95.4x104.9
Fuel Type	Petrol	Petrol	Petrol	Petrol	Petrol	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Fuel Supply - Injection System	MPFI	MPFI	MPFI	MPFI	MPFI	Common Rail	Common Rail	Common Rail	Common Rail	Common Rail	Common Rail
Power (kW) @ r/ min	94@4800	94@4800	155@5600	155@5600	155@5600	85@3600	85@3600	120@3600	120@3600	120@3600	120@3600
Torque (Nm) @ r/min	207@3200	207@3200	300@3200	300@3200	300@3200	280@1800-2200	280@1800-2200	360@1800-2800	333@1600-3200	360@1800-2800	333@1600-3200
Turbocharger	-	-	-	-	-	•	•	•	•	•	•
Intercooler	-	-	-	-	-	•	•	•	•	•	•
Engine Oil Sump Guard	•	•	•	•	•	•	•	•	•	•	•
<b>Transmission</b>											
Differential Lock: Electro-pneumatic	•	•	•	•	•	•	•	•	•	•	•
4WD Button Select - 2 Speed Transfer Case	-	•	-	•	•	-	•	-	-	•	•
Front Axle - Auto Locking Shift on the Fly	-	•	-	•	•	-	•	-	-	•	•
Transfer Case Guard	-	•	-	•	•	-	•	-	-	•	•
Automatic: 4 Speed	-	-	-	-	•	-	-	-	•	-	•
Gear Ratio: 1st	4.357	4.357	3.753	3.753	3.059	4.008	4.008	4.326	2.804	4.326	2.804
Gear Ratio: 2nd	2.502	2.502	2.258	2.258	1.625	2.301	2.301	2.557	1.532	2.557	1.532
Gear Ratio: 3rd	1.501	1.501	1.373	1.373	1.000	1.427	1.427	1.490	1.000	1.490	1.000
Gear Ratio: 4th	1.000	1.000	1.000	1.000	0.696	1.000	1.000	1.000	0.705	1.000	0.705
Gear Ratio: 5th	0.809	0.809	0.729	0.729	-	0.745	0.745	0.795	-	0.795	-
Gear Ratio: Reverse	3.970	3.970	3.672	3.672	2.294	3.651	3.651	3.942	2.394	3.942	2.394
Axle Ratio: Final Drive	4.875	5.125	4.300	4.300	4.555	4.111	4.100	3.727	4.100	3.727	4.100
Low Range Ratio		2.482		2.482	2.482		2.482			2.482	2.482
<b>Masses, Dimensions and other Key Measurements</b>											
GVM (kg)	2800	2900	2800	2900	2900	2800	2900	2800	2800	2900	2900
GCM (kg)	3750	4000	3750	4000	4000	3750	4000	3750	3750	4000	4000
Tare (kg)	1710	1810	1765	1920	1930	1830	1935	1900	1910	2000	2010
Payload (kg)	1090	1090	1035	980	970	970	965	900	890	900	890
GAW (kg) - Front	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300
GAW (kg) - Rear	1680	1680	1680	1680	1680	1680	1680	1680	1680	1680	1680
Legal Towing Capacity (kg): Unbraked Trailer	750	750	750	750	750	750	750	750	750	750	750
Legal Towing Capacity (kg): Trailer with Overrun Brake	950	1100	950	1100	1100	950	1100	950	950	1100	1100
Overall Length (mm)	5030	5030	5030	5030	5030	5030	5030	5030	5030	5030	5030



# DOUBLE CAB SPEC



Model	KB 240	KB 240	KB 360 V6	KB 360 V6	KB 360 V6	KB 250 D-TEQ	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LE	LE	LX	LX	LX	LE	LE	LX	LX	LX	LX
Drive Configuration	4x2	4x4	4x2	4x4	4x4 auto	4x2	4x4	4x2	4x2 auto	4x4	4x4 auto
Overall Length (mm) (Incl. Rear Step/Tow Bar Where Applicable)	5030	5030	5030	5030	5030	5030	5030	5030	5030	5030	5030
Overall Width (mm)	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
Overall Width (mm) (Incl. Mirrors)	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060	2060
Overall Height (mm)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Wheelbase (mm)	3050	3050	3050	3050	3050	3050	3050	3050	3050	3050	3050
Ground Clearance (mm) (Centre Differential)	224	224	206	206	206	224	224	206	206	206	206
Track: Front (mm)	1520	1520	1520	1520	1520	1520	1520	1520	1520	1520	1520
Track: Rear (mm)	1525	1525	1525	1525	1525	1525	1525	1525	1525	1525	1525
Loadbox: Length (mm)	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380
Loadbox: Width (mm)	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460	1460
Loadbox: Depth (mm)	480	480	480	480	480	480	480	480	480	480	480
Fuel Tank Capacity (litres)	76	76	76	76	76	76	76	76	76	76	76
Approach Angle	36°	36°	36°	36°	36°	36°	36°	36°	36°	36°	36°
Departure Angle	23°	23°	23°	23°	23°	23°	23°	23°	23°	23°	23°
Breakover Angle	158°	158°	158°	158°	158°	158°	158°	158°	158°	158°	158°
Turning Circle: Tyres (m)	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4
Turning Circle: Body (m)	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1	13.1
Steering Lock-to-lock	3.26	3.26	3.26	3.26	3.26	3.26	3.26	3.26	3.26	3.26	3.26
Steering Ratio	18.3	18.3	18.3	18.3	18.3	18.3	18.3	18.3	18.3	18.3	18.3
Wading Depth	500mm	500mm	500mm	500mm	500mm	500mm	500mm	500mm	500mm	500mm	500mm
<b>Vehicle Safety and Security</b>											
SRS Airbags: Driver and Passenger	•	•	•	•	•	•	•	•	•	•	•
ABS: 4 Sensor 3 Channel Anti-lock Braking System and EBD	•	•	•	•	•	•	•	•	•	•	•
Seat Belt Front: Inertia Reel Locking (3-point) with Adjustable Shoulder & Pretensioner	•	•	•	•	•	•	•	•	•	•	•
Seat Belt Rear: Side Inertia Reel Locking (3-point)	•	•	•	•	•	•	•	•	•	•	•
Seat Belt Rear: Centre Inertia Reel Locking (3-point)	•	•	•	•	•	•	•	•	•	•	•
Head Restraints Front - Adjustable & Active	•	•	•	•	•	•	•	•	•	•	•
Head Restraints Rear - Adjustable	•	•	•	•	•	•	•	•	•	•	•
Side Door Impact Beams	•	•	•	•	•	•	•	•	•	•	•
Aspherical Driver's Side Mirror with Split	•	•	•	•	•	•	•	•	•	•	•
Central Locking: Remote Activation (with Selective Unlock)	•	•	•	•	•	•	•	•	•	•	•
Audible Alarm System	•	•	•	•	•	•	•	•	•	•	•
Transponder Immobiliser System (Key Housed)	•	•	•	•	•	•	•	•	•	•	•
Automatic Door Lock: Over 30km/h	•	•	•	•	•	•	•	•	•	•	•
Rear Door Child Proof Locks - Manual Lock	•	•	•	•	•	•	•	•	•	•	•

# DOUBLE CAB SPEC



Model	KB 240	KB 240	KB 360 V6	KB 360 V6	KB 360 V6	KB 250 D-TEQ	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LE	LE	LX	LX	LX	LE	LE	LX	LX	LX	LX
Drive Configuration	4x2	4x4	4x2	4x4	4x4 auto	4x2	4x4	4x2	4x2 auto	4x4	4x4 auto
Spare Wheel Lock (Matched to Vehicle Lock Set)	•	•	•	•	•	•	•	•	•	•	•
<b>Wheels, Suspension and Brakes</b>											
Wheel Size	7Jx15	7Jx16	7Jx16	7Jx16	7Jx16	7Jx15	7Jx16	7Jx16	7Jx16	7Jx16	7Jx16
Tyre Size	245/75R15C	245/70R16C	245/70R16C	245/70R16C	245/70R16C	245/75R15C	245/70R16C	245/70R16C	245/70R16C	245/70R16C	245/70R16C
Alloy Wheels: 15"	•	-	-	-	-	•	-	-	-	-	-
Alloy Wheels: 16"	0	•	•	•	•	0	•	•	•	•	•
Front Disc Diameter	280mm	280mm	280mm	280mm	280mm	280mm	280mm	280mm	280mm	280mm	280mm
Rear Drum Diameter	295mm	295mm	295mm	295mm	295mm	295mm	295mm	295mm	295mm	295mm	295mm
Front & Rear Shocks	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised	Twin-tube Pressurised
Suspension - Front	High Ride Torsion Bar	Torsion Bar	High Ride Torsion Bar	Torsion Bar	Torsion Bar	High Ride Torsion Bar	Torsion Bar	High Ride Torsion Bar	High Ride Torsion Bar	Torsion Bar	Torsion Bar
<b>Interior Comfort and Convenience</b>											
Bucket Seats: Front with Backrest Adjust & Height Adjustable Driver Seat	•	•	•	•	•	•	•	•	•	•	•
Bench Seat: Rear with Tilttable Backrest	•	•	•	•	•	•	•	•	•	•	•
Map Pockets: Behind Front Seats	•	•	•	•	•	•	•	•	•	•	•
Full Cloth Seat Covering	•	•	-	-	-	•	•	-	-	-	-
Leather / Cloth Combination Trim	-	-	•	•	•	-	-	•	•	•	•
Silver Finish Hard Trim	-	-	•	•	•	-	-	•	•	•	•
Floor Cover: Carpet - with Driver Heel Mat	•	•	•	•	•	•	•	•	•	•	•
Driver's Left Footrest	•	•	•	•	•	•	•	•	•	•	•
Cruise Control	-	-	•	•	•	-	-	•	•	•	•
Steering: Power Assist	•	•	•	•	•	•	•	•	•	•	•
Urethane Steering with Airbag	•	•	-	-	-	•	•	-	-	-	-
Leather Steering with Airbag	-	-	•	•	•	-	-	•	•	•	•
Steering Column: Tilt	•	•	•	•	•	•	•	•	•	•	•
Power Windows - Front with Auto Down for Driver	•	•	•	•	•	•	•	•	•	•	•
Power Windows - Rear	•	•	•	•	•	•	•	•	•	•	•
Air Conditioner	•	•	•	•	•	•	•	•	•	•	•
Cabin Air Filter (Pollen)	•	•	•	•	•	•	•	•	•	•	•
Windscreen Tinted with Shadeband	•	•	•	•	•	•	•	•	•	•	•
Side Glass Tinted	•	•	•	•	•	•	•	•	•	•	•
Sliding Rear Window (Tinted)	•	•	•	•	•	•	•	•	•	•	•
Assist Grip Handle: Front	•	•	•	•	•	•	•	•	•	•	•
Assist Grip Handle: Rear	•	•	•	•	•	•	•	•	•	•	•
Front Gearshift Console with 2 Cupholders	•	•	•	•	•	•	•	•	•	•	•
Centre Storage Console	•	•	•	•	•	•	•	•	•	•	•
Illuminated & Lockable Glove Box	•	•	•	•	•	•	•	•	•	•	•

# DOUBLE CAB SPEC



Model	KB 240	KB 240	KB 360 V6	KB 360 V6	KB 360 V6	KB 250 D-TEQ	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LE	LE	LX	LX	LX	LE	LE	LX	LX	LX	LX
Drive Configuration	4x2	4x4	4x2	4x4	4x4 auto	4x2	4x4	4x2	4x2 auto	4x4	4x4 auto
Day / Night Rear View Mirror	•	•	•	•	•	•	•	•	•	•	•
Map Reading Lights - Front	•	•	•	•	•	•	•	•	•	•	•
Room Lamp Door Operated	•	•	•	•	•	•	•	•	•	•	•
Room Lamp Delay - Fade Up / Down	•	•	•	•	•	•	•	•	•	•	•
Coat Hook: Rear Driver & Passenger Side	•	•	•	•	•	•	•	•	•	•	•
Sunvisor Driver & Passenger Side	•	•	•	•	•	•	•	•	•	•	•
Vanity Mirror Passenger Side	•	•	•	•	•	•	•	•	•	•	•
Power Outlet on Dash	•	•	•	•	•	•	•	•	•	•	•
Headlamps "On" Warning Buzzer	•	•	•	•	•	•	•	•	•	•	•
Coolant Level Warning Buzzer	•	•	-	-	-	-	-	-	-	-	-
Digital Clock	•	•	•	•	•	•	•	•	•	•	•
Fuel Consumption and Outside Temperature Meter	-	-	-	-	-	-	-	•	•	•	•
Windscreen Wipers - Intermittent	•	•	-	-	-	•	•	-	-	-	-
Windscreen Wipers - Variable Intermittent	-	-	•	•	•	-	-	•	•	•	•
Remote Fuel Flap Release	•	•	•	•	•	•	•	•	•	•	•
Smoker Pack - Instrument Panel Mounted (Illuminated)	•	•	•	•	•	•	•	•	•	•	•
<b>Exterior Features</b>											
Metallic Paint	•	•	•	•	•	•	•	•	•	•	•
Front Fog Lamps	•	•	•	•	•	•	•	•	•	•	•
Roll Bar	•	•	•	•	•	•	•	•	•	•	•
Mudguards Front and Rear	•	•	•	•	•	•	•	•	•	•	•
Front Bumper: Grey Grained	•	•	-	-	-	•	•	-	-	-	-
Front Bumper: Body Colour	-	-	•	•	•	-	-	•	•	•	•
Running Board - Full Length	-	-	•	•	•	-	-	•	•	•	•
High Opulent Full Width Rear Step Bumper with Tow Pack	•	•	•	•	•	•	•	•	•	•	•
Body Side Mouldings: Grey	•	•	-	-	-	•	•	-	-	-	-
Body Side Mouldings: Body Colour	-	-	•	•	•	-	-	•	•	•	•
Wheel Arch Mouldings: Grey Grained	•	•	-	-	-	•	•	-	-	-	-
Wheel Arch Mouldings: Body Colour	-	-	•	•	•	-	-	•	•	•	•
Rear View Mirror: Black Power Folding	•	•	-	-	-	•	•	-	-	-	-
Rear View Mirror: Chrome Power Folding with Indicator	-	-	•	•	•	-	-	•	•	•	•
<b>In Car Entertainment</b>											
Radio/CD/MP3 + CD Changer Control	•	•	•	•	•	•	•	•	•	•	•
Front Speakers - Front Doors	•	•	•	•	•	•	•	•	•	•	•
Tweeters - Front Doors	-	-	•	•	•	-	-	•	•	•	•
Rear Speakers - Rear Doors	•	•	•	•	•	•	•	•	•	•	•
Antenna - B stng	•	•	•	•	•	•	•	•	•	•	•

# DOUBLE CAB SPEC



Model	KB 240	KB 240	KB 360 V6	KB 360 V6	KB 360 V6	KB 250 D-TEQ	KB 250 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ	KB 300 D-TEQ
Opulence	LE	LE	LX	LX	LX	LE	LE	LX	LX	LX	LX
Drive Configuration	4x2	4x4	4x2	4x4	4x4 auto	4x2	4x4	4x2	4x2 auto	4x4	4x4 auto
Warranty, Service and Support											
Service Plan - 5Year / 90 000km	•	•	•	•	•	•	•	•	•	•	•
Service	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Oil Change	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Warranty	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km
Roadside Assistance	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km	5 year / 100 000km
Anti-corrosion	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

Standard	•
Optional	O
Not Available	-

Disclaimer: The information contained in this spec sheet was accurate at the time of going to press (1 November 2007). Specifications and equipment are subject to change without prior notice. Please contact your Isuzu retailer for exact information.

[www.isuzu.co.za](http://www.isuzu.co.za) / 0800 422 7777

© General Motors South Africa 2007

